

WILDEN®

WILDEN PRODUCT OFFERING



Pump Series	Description	Wetted Path	Construction	Size							Certification	
				6 mm 1/4"	13 mm 1/2"	25 mm 1"	38 mm 1-1/2"	51 mm 2"	76 mm 3"	102 mm 4"		
Standard Series	Pro-Flo® SHIFT Series (PS or XPS) Max Flow Rates: 60.2 lpm - 1048 lpm (15.9 gpm - 277 gpm)	Polypropylene	Clamped				☒	☒				CE CE (X)
			Bolted				☒	☒	☒			
		PVDF	Clamped				☒					
			Bolted				☒	☒	☒			
		Aluminum	Clamped		☒		☒	☒	☒			
			Bolted			☒	☒	☒	☒			
		Stainless Steel	Clamped		☒		☒	☒	☒	☒		
	Bolted				☒	☒	☒	☒	☒			
	Ductile Iron	Clamped				☒			☒	☒		
		Bolted				☒	☒	☒	☒			
		Alloy C	Clamped		☒							
	Bolted							☒	☒	☒		
								☒	☒	☒		
								☒	☒	☒		
Pro-Flo® Series (P) Max Flow Rates: 16.7 lpm - 878 lpm (4.4 gpm - 232 gpm)	Polypropylene	Clamped	☒	☒	☒	☒	☒			CE		
		Bolted	☒	☒	☒	☒	☒	☒				
	PVDF	Clamped	☒	☒	☒	☒						
		Bolted	☒	☒	☒	☒	☒	☒				
	Aluminum	Clamped	☒	☒	☒	☒	☒	☒				
		Bolted	☒	☒	☒	☒	☒	☒				
	Stainless Steel	Clamped	☒	☒	☒	☒	☒	☒				
Bolted		☒	☒	☒	☒	☒	☒					
Ductile Iron	Bolted			☒	☒	☒	☒					
Hygienic & Sanitary Applications	Saniflo™ Hygienic™ Series (HS) Pumps Max Flow Rates: 357 lpm - 844 lpm (94 gpm - 223 gpm)	Stainless Steel	Clamped			☒	☒	☒	☒	USP CLASS VI FDA CE		
			Saniflo™ FDA Pumps Max Flow Rates: 58.7 lpm - 927 lpm (15.5 gpm - 245 gpm)	Stainless Steel	Clamped		☒	☒	☒		☒	*PS Models Only FDA CE (X)*
Electronic Control Applications	Accu-Flo™ Pumps (A) Max Flow Rates: 11.7 lpm - 170 lpm (3.1 gpm - 45 gpm)	Polypropylene	Clamped	☒	☒	☒				CE		
			Bolted	☒	☒	☒						
		PVDF	Clamped	☒	☒	☒						
			Bolted	☒	☒	☒						
		Aluminum	Clamped	☒	☒	☒						
Alloy C	Clamped		☒	☒								
Utility Applications	Turbo-Flo™ Pumps (T) Max Flow Rates: 54.9 lpm - 1041 lpm (14.5 gpm - 275 gpm)	Aluminum	Clamped		☒		☒	☒	☒	CE		
		Ductile Iron	Clamped				☒	☒	☒		☒	
High-Pressure Applications	High-Pressure Pumps (H****S) Max Flow Rates: 93.9 lpm - 291 lpm (24.8 gpm - 77 gpm)	Alloy C	Bolted					3:1		* 76 mm (3") not ATEX compliant		
		Aluminum	Bolted				2:1					
		Stainless Steel	Bolted			3:1	2:1	3:1	3:1 HS Series			
		Ductile Iron	Bolted			3:1		3:1				
Mining Applications	Stallion® Pumps Max Flow Rates: 307 lpm - 764 lpm (81 gpm - 202 gpm)	Aluminum	Clamped				☒	☒	☒	CE (X)		
		Ductile Iron	Clamped				☒	☒				
Large Solids Handling Applications	Brahma™ Pumps Max Flow Rates: 640 lpm - 977 lpm (169 gpm - 258 gpm)	Aluminum	Bolted				☒	☒		CE (X)		
		Ductile Iron	Bolted				☒	☒				
Natural Gas-Operated Applications	GPS Pumps Max Flow Rates: 61.7 lpm - 993 lpm (16.3 gpm - 246 gpm)	Aluminum	Clamped		☒*					* Available as GPX models, GPS models available soon		
			Bolted			☒*	☒	☒	☒			
		Stainless Steel	Clamped		☒*							
			Bolted			☒*	☒	☒	☒			
Fuel Transfer Applications	UL Pumps Max Flow Rates: 60.2 lpm - 212 lpm (15.9 gpm - 56 gpm)	Aluminum	Clamped		☒					UL CE (X)		
			Bolted			☒						
		Stainless Steel	Clamped		☒							
			Bolted			☒						

Type	Model Guide						
	6mm (1/4")	13mm (1/2")	25mm (1")	38mm (1-1/2")	51mm (2")	76mm (3")	102mm (4")
Clamped Plastic and Metal	.025	1	2	4	8	15	20
Bolted Plastic	25	100	200	400	800	1500	-
Bolted Metal	-	-	220/230	420/430	820/830	1520/1530	-
	X20 = Threaded			X30 = Flanged			

Expand Your Operation and Performance

- Upgrade to Chem-Fuse and Pure-Fuse integral piston diaphragms for up to 10 times the diaphragm life, elimination of potential leak point and easy cleanability
- Keep money in your customers' pockets by using Pro-Flo SHIFT (up to 60% more efficient than competitors)
- Achieve peak performance with authentic Wilden parts and accessories